



CLEARCUBE

www.clearcube.com

Serial Command Port (C/Port) for CPU Blades

Remote Desktop Unit with Serial Peripheral Interfaces and 200 m Support

Located at the user's desktop, this remote unit enables users to interface with their rack-mounted CPU Blade. ClearCube's Serial C/Port is a perfect solution for those wanting to synchronize their PDAs, add a touch screen, use a barcode scanner, or hook up many industrial devices. All of this is accomplished without the IT manager having to sacrifice the security that is obtained with the elimination of I/O devices like floppy and CD-ROM drives. A user can still connect standard peripherals such as keyboard, mouse, microphone, and speakers at the desktop without having a box PC at their feet or the temptation to remove information or assets. The Serial C/Port also supports connections up to 200m from the CPU Blade.

The Serial C/Port requires no special software, has no moving parts that can fail, contains no removable parts that might encourage user tampering or theft, and connects quickly and easily to standard peripherals. With its compact design, the Serial C/Port can rest on the desk or be mounted underneath the desk with an optional mounting bracket. The serial C/Port is available with or without a keyboard and mouse.

ClearCube's architecture combines CPU Blades, Cages, C/Ports, and advanced systems management to create a managed desktop environment that delivers exceptional security, reliability, manageability, and space savings with a lower total cost of ownership for enterprise computing.

ClearCube Serial C/Port Specifications

Connections

- Standard PS/2 Mouse and Intelli-mouse
- Standard PS/2 Keyboard
- Audio In/Out: stereo audio output supports 32 ohm headsets or amplified speaker system
- Power Connector
- VGA monitor connection (standard DB-15)
- RS-232a Serial Port
- RJ-45 for CPU Blade connection
- Requires full Category 5 cable with all four pairs



Serial C/Port



Serial C/Port Rear View

Dimensions: 1.4"H x 3.4"D x 5.5"W

Environment: Stationary installation, 0-35 deg. C

- Standard 120V power adapter included
- Sharpness and tuning adjustments for video
- Up to 200 meters (660 ft.) distance to CPU Blade
- Under-desk mounting bracket (optional)

Ordering Information

Use the following part numbers to order your ClearCube C/Port:

CPT-XSR2	Serial C/Port with 200 m support
CPT-XSR2-KM	Serial C/Port with 200 m support including keyboard and wheel mouse
CPT-MNTA	Under-desk mounting adapter for C/Port